

► **XF SERIES
HIGH-PERFORMANCE
SOFTMOUNT
WASHER-EXTRACTOR**



Precision-engineered softmount design: industry-leading vibration control, more compact structure, superior fabric care, and service-friendly maintenance.

▼ **Advantages And Benefits**

- ⌚ Proprietary multi-point vertical suspension structure absorbs >95% vibration.
- 🔧 New handles and safety door locks for more comfortable operation, simpler maintenance, and enhanced safety.
- ⚙️ Variable-frequency drive for precise control of wash and extraction speeds.
- 🌀 3D honeycomb-shaped drum protects textiles, improves cleanliness and accelerates drainage.
- 🛡️ Corrosion-protected wet-area components for longer service life.

- ⌚ Triple water seals and oversized drum shaft for durability under extreme conditions.
- ⚙️ Extra-large door and ergonomic layout for fast, low-effort loading and easy maintenance.
- 👤 Four-compartment manual dosing with five automatic dosing inlets.

► **Options**

- ① Steam heating; electric heating; dual heating.
- ② Front-tilt models with 60/100/120 kg capacity.

▼ **7-inch Touchscreen Control**

- 50 freely programmable programs
- Multiple languages
- USB program transfer
- Manual/automatic mode switching
- Operating status logging



Model		XF40		XF60		XF80		XF100		XF120	
Washing Capacity		Kg	40	60	60 (Tilt)	80	100	100 (Tilt)	120	120 (Tilt)	
Dimension											
Width	mm	1180	1487	1547	1672	1672	1727	1774	1850		
Depth	mm	1399	1482	1568	1581	1748	1823	1828	1895		
Height	mm	1520	1820	1984	1986	1986	2110	2092	2580		
Packing dimension											
Width	mm	1200	1507	1567	1692	1692	1747	1850		Body1950 Base1950	
Depth	mm	1419	1502	1588	1601	1768	1843	1825		Body1995 Base800	
Height	mm	1640	1980	2104	2106	2106	2230	2285		Body1690 Base750	
Weight											
Net	Kg	1140	1840	2040	2100	2600	2800	3170	3580		
Washing drum											
Diameter	mm	903	1078	1078	1240	1240	1240	1310	1310		
Depth	mm	626	656	656	673	840	840	816	816		
Volume	dm ³	400	598	598	812	1014	1014	1100	1100		
Door Opening	mm	423	567	567	682	682	682	686	686		
Electric											
Voltage	380V/50/60Hz/3, 220V/50/60Hz/3, Contact us for other voltages										
Motor	kW	4	5.5	5.5	5.5	7.5	7.5	11	11		
Heating Element	kW	30	30	30	30	60	60	60	60		
Washing											
Washing Speed	RPM	30	30	30	30	29	29	29	29		
Extraction Speed	RPM	840	810	810	760	760	760	660	660		
G-Force		350	400	400	400	400	400	300	300		
Utility connection											
Water inlet (cold/hot)	inch	2*1"	2*1 1/2"	2*1 1/2"	2*1 1/2"	2*1 1/2"	2*1 1/2"	2*2"	2*2"		
Chemical flushing	inch					3/4"		/	/		
Water pressure	Mpa					0.1-0.3					
Temperature Max	°C					90					
Drainage	mm	Φ76	Φ110	Φ110	Φ110	2*Φ110	2*Φ110	2*Φ125	2*Φ125		
Steam connection	inch	3/4"	1"	1"	1"	1"	1"	1"	1"		
Steam pressure	Mpa					0.4~0.6					
Compress air connection	mm					Φ8					
Compress air	Mpa					Φ8 mm at 0.4~0.8Mpa					

*OASIS preserves the right to change the machines and specifications at any time without prior notice.









Jinan Oasis Dry Cleaning and Laundry Equipment Co.,Ltd.
 Tel: +86-531-85701288 85711288
 E-mail: inquiry@oasisle.com
 Http://www.oasislaundrygroup.com
 Add: No.39, Lan Xiang Middle Road, Jinan City, China